

**FINANCIAL BID (PART-II)
(To be filled online)**

Annexure-'D'

Bill of Quantity

ARM work of Regional Office with staff qtrs. and Branch offices with staff qtrs. in Rajasthan-2019-20.

Abstract

Sr. No.	Item	Amount (Rs.)
1	Cost of Civil Work (a)	
2	Cost of Sanitary Work (b)	
3	Cost of Electrical Work (c)	
4	Labour (Supply & Service Work) (d)	
5	Horticulture (Lump-Sum) (10% of a, Approx.)	
6	<u>Market Rate Items :-</u> On producing as per actual bill up to Rs-1000/Item and more than Rs-1000/Item CA has to submitted minimum three quotation. (LS Amount) (f) (15% of a+b, Approx.)	
	Total (a+b+c+d+e+f)	

**FINANCIAL BID (PART-I)
(To be filled online)**

Annexure-'D'

Bill of Quantity

ARM work of Regional Office with staff qtrs. and Branch offices with staff qtrs. in Rajasthan-2019-20.

Supply of Labour

S.No	(A) Supply and Services of workers. (Regular)	Total Nos.	Rate (Per Day) (a)	ESI Employers Contribution @ (4.75%) of (a) (b)**	EPF employers contribution @ 13.36 % of (a) (c)**	Uniform, Safety shoes, Badges and tools and plants @ 5% of (a) (d)**	Total (a+b+c+d)	Total Amount
	Maintenance an office in space provided by ESIC and attending to Repair and Maintenance work the above maintenance staff with all required helpers, tools and plants							
1	Supervisor	1	527	25	70	26	649	16874
2	Plumber	1	527	25	70	26	649	16874
3	Pump Operator	1	527	25	70	26	649	16874
4	Beldar/Helper	1	466	22	62	23	574	14924
5	Electrician	1	527	25	70	26	649	16874
6	Mali	1	527	25	70	26	649	16874
(A) Total Rs.								99294.00
Contractor Profit in Percentage (i/c All Tax (+/-) will be quoted by bidder on 'A'								
Amount of Contractor Profit (+/-) (+/-(i) of 'A'=B								
Total (A+B)=C								
Total Amount for 12 Month(Cx12)=D								

S.No	(B) Supply and Services of workers. (On Call)	Total Nos.	Rate (Per Day) (a)	ESI Employers Contribution @ (4.75%) of (a) (b)**	EPF employers contribution @ 13.36 % of (a) (c)**	Uniform, Safety shoes, Badges and tools and plants @ 5% of (a) (d)**	Total (a + b + c + d)	Total Amount for 10 Days in one Months
1	Mason	10 nos per month	527	25	70	26	649	6490
2	Carpenter	10 nos per month	527	25	70	26	649	6490
3	Welder	10 nos per month	527	25	70	26	649	6490
4	Beldar/Helper	10 nos per month	466	22	62	23	574	5740
(A) Total Rs.								25210.00
Contractor Profit in Percentage (i/c All Tax (+/-) will be quoted by bidder on 'a'								
Amount of Contractor Profit (+/-) (+/-(ii)of 'a'=b								
Total (a+b)=c								
Total Amount for 12 Month(cx12)=d								
Total Amount (D+d)								
Note:- On call manpower will be provided only actual requirement and recommended by ESIC.								

**FINANCIAL BID (PART-II)
(To be filled online)**

Annexure-'D'

Bill of Quantity

ARM work of Regional Office with staff qtrs. and Branch offices with staff qtrs. in Rajasthan-2019-20.

CIVIL WORK						
Sr No.	Code No.	Item Description	Unit	Qty	Rate (Rs.)	Amount (Rs.)
		Earth Work				
1	2.1.1	Earth work in surface excavation not exceeding 30 cm in depth but exceeding 1.5 m in width as well as 10 sqm on plan including disposal of excavated earth upto 50 m and lift upto 1.5 m, disposed soil to be levelled and neatly dressed : All kinds of soil	100 sqm	100		
2	4.1	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :				
	4.1.8	1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size)	CUM	15		
	4.1.3	"1:2:4 (1 cement : 2 coarse sand (zone-III) : 4 graded stone aggregate 20 mm nominal size).	CUM	45		
3	5.22.6	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars	Kg	200		
4	6.2.2	Brick work with common burnt clay modular bricks of class designation 7.5 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand).	cum	25		
5	7.1.1	Random rubble masonry with hard stone in superstructure above plinth level and upto floor five level, including leveling up with cement concrete 1:6:12 (1 cement : 6 coarse sand : 12 graded stone aggregate 20 mm nominal size) at window sills, ceiling level and the like. Cement mortar 1:6 (1 cement : 6 coarse sand)	cum	10		

6	7.40.1	Providing and fixing dry cladding upto 10 metre heights with 30 mm thick gang saw cut stone with (machine cut edges) of uniform colour and size upto 1mx1m, fixed to structural steel frame work and/ or with the help of cramps, pins etc. and sealing the joints with approved weather sealant as per Architectural drawing and direction of Engineer-in-charge. (The steel frame work, stainless steel cramps and pins etc. shall be paid for separately). Red sand stone - 30mm thick gang saw cut stone	sqm	10		
7	8.2	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills , facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels.				
	8.2.1	Raj Nagar Plain white marble/ Udaipur green marble/ Zebra black marble				
	8.2.1.1	Area of slab upto 0.50 sqm	sqm	5		
	8.2.1.2	Area of slab over 0.50 sqm	sqm	5		
	8.2.2	Granite of any colour and shade				
	8.2.2.1	Area of slab upto 0.50 sqm	sqm	5		
	8.2.2.2	Area of slab over 0.50 sqm	sqm	5		
		WOOD & PVC WORK				
8	9.20.1	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) decorative type, core of block board construction with frame of 1st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	sqm	10		
9	9.21.1	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters: 35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	sqm	10		

10	9.118.1	24 mm thick factory made PVC door shutters made of styles and rails of a uPVC hollow section of size 59x24 mm and wall thickness 2 mm (± 0.2 mm) with inbuilt edging on both sides. The styles and rails mitred and joint at the corners by means of M.S. galvanised/plastic brackets of size 75x220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 20x20 mm and 1 mm (± 0.1 mm) wall thickness. The lock rail made up of 'H' section, a uPVC hollow section of size 100x24 mm and 2 mm (± 0.2 mm) wall thickness, fixed to the shutter styles by means of plastic/galvanised M.S. 'U' cleats. The shutter frame filled with a uPVC multi-chambered single panel of size not less than 620 mm, having overall thickness of 20 mm and 1 mm (± 0.1 mm) wall thickness. The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer-in-charge. (For W.C. and bathroom door shutter).	sqm	20		
11	9.142.1	Providing and fixing PVC Door Frame of size 50x47 mm with a wall thickness of 5 mm (± 0.2 mm), made out of single piece extruded PVC profile, with mitred cut joints and joint with 2 nos of PVC bracket of size 190 mm x 100 mm long arms of cross section size 35 x 15 mm & self driven self tapping screws, the vertical door profiles to be reinforced with 40x20 mm M.S. rectangular tube of 0.8 mm, including providing EPDM rubber gasket weather seal throughout the frame, including jointing 5 mm PVC frame strip with PVC solvent cement on the back of the profile. The door frame to be fixed to the wall using 8 x 100 mm long anchor fasteners complete, all as per manufacturer's specification and direction of Engineer-in-charge. Non decorative finish (matt finish)	metre	10		
12	9.101.2	Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete. Twin rubber stopper	each	100		
13	9.7.7.1	Float glass panes:- 4 mm thick glass pane	sqm	35		
14	10.29.1	Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete. Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides	sqm	40		
15	11.26.1	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1 : 4 (1 cement : 4 coarse sand) :- 25 mm thick	sqm	20		

16	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	sqm	50		
17	11.37	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), including pointing the joints with white cement and matching pigment etc, complete.	sqm	50		
18	11.41.2	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS : 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), including grouting the joints with white cement and matching pigments etc., Complete. Size of Tile 600x600 mm	sqm	15		
19	12.31.1	Providing 10 mm thick plaster of Paris (gypsum anhydrous) ceiling up to a height of 5 m above floor level, over first class kail wood strips 25x6 mm with 10 mm gap in between and reinforced with rabbit wire mesh fixed to wooden frame (frame work to be paid separately):- Flat surfaces	sqm	10		
20	12.41.2	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed Pipes. 110 mm diameter	metre	50		
21	12.42.4.2	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS :5382, leaving 10 mm gap for thermal expansion.Single tee without door:- 110x110x110 mm	each	50		

22	12.43.2	Providing and fixing unplasticised -PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length, including cutting brick work and fixing in cement mortar 1:4 (1 cement : 4 coarse sand) and making good the wall etc. complete. 110 mm diameter	each	50		
23	14.1.2	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground within 50 metres Lead :- With cement mortar 1:4 (1cement: 4 coarse sand)	sqm	50		
24	13.26	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	sqm	500		
25	14.5.1	Renewing glass panes, with putty and nails wherever necessary including racking out the old putty:- Float glass panes of thickness 4 mm	sqm	30		
26	14.9	Renewal of old putty of glass panes (length)	metre	30		
27	14.10	Refixing old glass panes with putty and nails	sqm	30		
28	14.29	Providing and fixing M.S. round or square bars with M.S. flats at required spacing in wooden frames of windows and clerestory windows.	kg	100		
29	14.43	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	sqm	1500		
30	14.42.1	White washing with lime to give an even shade :- Old work (two or more coats)	sqm	100		
31	14.45.1	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade :- Old work (one or more coats)	sqm	7000		
32	13.41.1	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade :- New work (two or more coats) over and including water tinnable priming coat with cement primer	sqm	250		
34	14.54.1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :- One or more coats on old work	sqm	200		

35	14.66.1	Finishing walls with Acrylic Smooth exterior paint of required shade :- Old work (Two or more coat applied @ 1.67 ltr/ 10 sqm) on existing cement paint surface	sqm	5000		
36	14.75A	Cleaning of terrace/loft water storage tank (inside surface area) upto 2000 litre capacity at all heights with coconut brushes, duster etc., removal of silt, rubbish from the tank and cleaning the tank with fresh water disinfecting with bleaching powder @ 0.5gm per litre capacity of tank, including marking the date of cleaning on the side of tank body with the help of stencil and paint and disposing of malba, all complete as per direction of Engineer-in-Charge. (The old date already written on tank should be removed with paint remover or black paint and if date is not written with the stencil or old date is not removed deduction will be made @ Rs. 0.10 per litre if during cleaning any GI fittings or ball cock is damaged that is to be repaired by contractor at his own cost and nothing extra will be paid on this account)	litre	10000		
37	14.82	Dismantling W.C. Pan of all sizes including disposal of dismantled materials i/c malba all complete as per directions of Engineer-in-Charge.	each	20		
38	15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts Involved.	cum	50		
39	16.68	Providing and laying 60mm thick factory made cement concrete interlocking paver block of M -30 grade made by block making machine with strong vibratory compaction, of approved size, design & shape, laid in required colour and pattern over and including 50mm thick compacted bed of coarse sand, filling the joints with fine sand etc. all complete as per the direction of Engineer-in-charge.	sqm	50		

40	17.1.1	Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:-White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests	each	10		
41	17.2.1	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever Required :- W.C. pan with ISI marked white solid plastic seat and lid	each	5		
42	17.7.1	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever Require:- White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps	each	10		
43	17.34.1	Providing and fixing toilet paper holder :- C.P. Brass	each	25		
44	21.13	Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	each	15		
45	22.14.1	Grading roof for water proofing treatment with: Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	cum	10		
45	9.100.1	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :- 125 mm	each	100		
Total (Rs.)						

**FINANCIAL BID (PART-II)
(To be filled online)**

Annexure-'D'

Bill of Quantity

ARM work of Regional Office with staff qtrs. and Branch offices with staff qtrs. in Rajasthan-2019-20.

Electrical Work

Sr No.	Code No.	Item Description	Unit	Qty	Rate (Rs.)	Amount (Rs.)
1	1.8	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with piano type switch, phenolic laminated sheet, suitable size M.S. box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.				
	1.8.1	Group A	Point	20		
	1.8.2	Group B	Point	20		
	1.8.3	Group C	Point	20		
2	1.21	Supplying and fixing of following sizes of medium class PVC conduit along with accessories in surface/recess including cutting the wall and making good the same in case of recessed conduit as required.				
	1.21.1	20 mm	Metre	35		
	1.21.2	25 mm	Metre	35		

3	1.17	Supplying and drawing following sizes of FRLS PVC insulated copper conductor, single core cable in the existing surface/ recessed steel / PVC conduit as required.				
	1.17.1	1 x 1.5 sq. mm	Metre	50		
	1.17.11	2 x 2.5 sq. mm	Metre	35		
	1.17.20	2 x 4 sq. mm	Metre	20		
	1.17.29	2 x 6 sq. mm	Metre	20		
4	1.22	Supplying and fixing metal box of following sizes (nominal size) on surface or in recess with suitable size of phenolic laminated sheet cover in front including painting etc as required.				
	1.22.1	75 mm X 75 mm X 60 mm deep	Each	15		
	1.22.3	150 mm X 75 mm X 60 mm deep	Each	10		
5	1.23	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required.				
	1.23.1	5/6 amps switch	Each	50		
	1.23.2	2 way 5/6 amps switch	Each	50		
	1.23.3	15/16 amp switch	Each	50		
	1.23.4	3 pin 5/6 amp socket outlet	Each	50		
	1.23.5	6 pin 15/16 amp socket outlet	Each	50		
	1.23.8	Bell push	Each	50		
6	1.25	Supplying and fixing stepped type electronic fan regulator on the existing modular plate switch box including connections but excluding modular plate etc. as required.	Each	100		

7	1.33	Supplying and fixing 3 pin, 5 amp ceiling rose on the existing junction box/ wooden block including connection etc as required.	Each	50		
	1.34	Supply & Fixing brass batton angle holder including connection etc.	Each	50		
8	1.38	Supplying and fixing call bell/ buzzer suitable for single phase, 230 volts, complete as required.	Each	10		
9	2.1	Providing and fixing following capacity TP&N disconnecter fuse switch unit inside the existing panel board with ISI marked HRC fuses including drilling holes in cubicle panel, making onnections, etc. as required.				
	2.1.1	32 Amp TP&N	Each	5		
	2.1.2	63 Amp TP&N	Each	3		
10	2.2	Providing and fixing following rating and breaking capacity and pole MCCB with thermomagnetic release and terminal spreaders in existing cubicle panel board including drilling holes in cubicle panel, making connections, etc. as required.				
	2.2.1	100 A, 16 kA,TPMCCB	Each	5		
	2.2.2	125 A, 16 kA,TPMCCB	Each	5		
	2.2.9	400 A, 35 kA,TPMCCB	Each	3		
	2.2.13	100 A, 30kA, FPMCCB	Each	5		
	2.2.14	125 A, 36kA, FPMCCB	Each	5		
	2.2.18	400 A, 50kA, FPMCCB	Each	3		

11	2.10.1	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. Single pole	Each	20		
12	5.1	Earthing with G.I. earth pipe 4.5 meter long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. (but without charcoal/ coke and salt) as required.	Set	10		
13	11.1	Erection of RCC/ PCC pole of following length in brick ballast and ramming the foundation, finishing with 150 mm thick cement concrete (1:3:6) layer on top with including excavation and refilling etc. as required.				
	11.1.1	Above 4.5 meter and upto 6.5 meter	Each	10		
	11.1.2	Above 6.5 meter and upto 8.0 meter	Each	10		
	11.1.3	Above 8.0 meter and upto 11.0 meter	Each	5		
	11.1.4	Above 11.00 meter and upto 13.00 meter	Each	5		
Total (A)						
Supply Items						
1	1401	Celling 3 pin 5 amp ISI mark	Each	50		
2	1431	S.P 5/6 amp one way switch Piano type ISI mark	Each	50		
3	1432	S.P 5/6 amp two way switch Piano type ISI mark	Each	50		
4	1433	S.P 15/16 amp one way switch Piano type ISI mark	Each	50		

5	1434	3 pin 5/6 amp socket outlet piano type ISI mark	Each	50		
6	1435	3 pin 15/16 & 5/6 amp socket outlet piano type ISI mark	Each	50		
7	1436	Bell Push Piano type	Each	50		
8	1437	Telephon Socket outlet piano type	Each	50		
9	1442	Brass batten angle holder	Each	50		
10	1444	Call bell burzer single phase	Each	25		
11	1452	PVC batton angle holde	Each	50		
12	1402	S.P 5/6 amp one way switch Modular type ISI mark	Each	50		
13	1403	S.P 5/6 amp two way switch Modular type ISI mark	Each	50		
14	1404	S.P 15/16 amp one way switch Modular type ISI mark	Each	50		
15	1405	3 pin 5/6 amp socket outlet modular type ISI mark	Each	50		
16	1406	6 pin 15/16 amp socket outlet modular type ISI mark	Each	50		
17	MR	Providing & Fixing LED Bulb 10 Watt	Each	100		
18	MR	Providing & Fixing 25 watt LED Street Light complete with all accessories	Each	10		
19	MR	Providing & Fixing 45 watt LED Street Light complete with all accessories	Each	10		
20	MR	Providing & Fixing Dome Light with bulb complete with all accessories	Each	10		
21	MR	Providing & Fixing 18 watt LED tube Light complete with all accessories	Each	200		
					Total (B)	
					Grand Total (A+B)	

**FINANCIAL BID (PART-II)
(To be filled online)**

Annexure-'D'

Bill of Quantity

ARM work of Regional Office with staff qtrs. and Branch offices with staff qtrs. in Rajasthan-2019-20.

Supply of Sanitary Items

Sr No.	Code No.	Item Description	Unit	Qty	Rate (Rs.)	Amount (Rs.)
1	7257	Supply of C.P. Brass bibcock 15 mm	each	75		
2	7259	Supply of C.P. Brass long body bibcock 15 mm	each	75		
3	7260	Supply of C.P. Brass stop cock (concealed) 15 mm	each	75		
4	7261	Supply of C.P. Brass angle valve 15 mm	each	75		
5	1392	Supply of Mirror of superior make glass 60x45 cm	each	70		
6	1532	Supply of Flush pipe with union spreaders and clamps all in C.P. brass for single stall	each	75		
7	1545	Supply of G.I. pipes 15 mm dia	metre	75		
8	1546	Supply of G.I. pipes 20 mm dia	metre	50		
9	1547	Supply of G.I. pipes 25 mm dia	metre	50		
10	1548	Supply of G.I. pipes 32 mm dia	metre	25		
11	1549	Supply of G.I. pipes 40 mm dia	metre	25		
12	1550	Supply of G.I. pipes 50 mm dia	metre	25		
13	1551	Supply of G.I. pipes 65 mm dia	metre	25		
14	1614	Supply of G.I. inlet connection	each	25		
15	1641	Supply of G.I. Union 15 mm nominal bore	each	50		
16	1642	Supply of G.I. Union 20 mm nominal bore	each	50		
17	1643	Supply of G.I. Union 25 mm nominal bore	each	50		
18	1649	Supply of Polyethylene water storage tank with cover and suitable locking Arrangement	per litre	10000		

19	1689	Supply of Unplasticised P.V.C. connection pipe with brass union 45 cm long 15 mm bore	each	100		
20	1875	Supply of White plastic seat (solid) with lid C.P. brass hinges and rubber buffers	each	25		
21	1879	Supply of Shower rose C.P.brass for 15 to 20 mm inlet 150 mm dia	each	25		
22	1881	Supply of Spun yarn	kilogram	25		
23	1927	Supply of Brass full way valve with C.I. wheel (screwed end) 25 mm dia	each	25		
24	1928	Supply of Brass full way valve with C.I. wheel (screwed end) 32 mm dia	each	25		
25	1951	Supply of C.P. brass waste 32 mm	each	25		
26	1952	Supply of C.P. brass waste 40 mm	each	25		
27	7763	Supply of Water supply tanker of 5000 litre capacity	each	10		
28	7018	Supply of Joint tape roll	each	100		
29	7095	Supply of Stainless steel kitchen sink - with drain board bowl depth 250 mm	each	5		
30	7115	Rectangular shape 1500x450 mm Mirror with Plastic moulded frame	each	10		
31	7117	Semi Rigid PVC waste pipe for sink and wash basin 32 mm dia with length not less than 700 mm i/c PVC waste fittings	each	50		
32	7188	uPVC pipes 75mm (working pressure 4 kg / cm ²) Single socketed pipe mm dia	Rmt	50		
33	7189	uPVC pipes 110mm (working pressure 4 kg / cm ²) Single socketed pipe mm dia	Rmt	50		
34	7358	Flushing Cistern P.V.C. 10 litre capacity (low level) (White) (with fittings, accessories and flush pipe)	each	25		
35	7400	15 mm PTMT bib cock	each	25		

36	7402	15 mm PTMT bib-cock long body with flange	each	20		
37	7406	PTMT pillar cock	each	20		
38	7491	PTMT - Waste Coupling 31/32 mm	each	20		
39	7429	Kickers	Rmt	10		
40	1213	Water proofing materials	kilogram	50		
						Total Rs.